Trimline 83 series

CREATES A LUXURIOUS AMBIENCE IN ANY ROOM





This fireplace will be a majestic eyecatcher in your space. It's extra tall, giving it extra presence. It fits within a wide range of interiors. What statement do you want to make with it?

The standard burner bed for the Trimline 83 series is made of wooden logs, and the standard interior has a slatted design. On top of that, it comes with the Ecomax remote control and you have the options of adding Wi-Fi-control with our Trimline Fires app.

Product specifications

FEATURES

1

Balanced flue gas fire



Front model



Corner left



Corner right



Panoramic model



Double burner woodlogs



Ecomax remote control



Antracite steel panel



Wide trims

OPTIONALS



LED glowing fuel bed



Wall bracket remote

trimline



Domotica smart





Wall switch





Set for app control

Puck control




Anti reflective glass



Mains adapter GV60



_



Ecomax remote control


For absolute ease of use all appliances are supplied with an Ecomax remote system that controls the fire at the touch of a button.





For that extra WOW factor, there is also an option to upgrade to a black glass lining within the combustion chamber which offers a remarkable effect of added depth and detail. Other available upgrades also include Wi-Fi, black glass interior and alternative frame options.











	T: 1: 00 5 ./0 /D				
Appliance name	Trimline 83 Front/Corner/Panoramic				
Appliance type	Balanced flue built-in/freestanding gas fires (C11, C31, C91)				
Purpose	Ambient heating, real flames				
Engine identification	1180(F), 1181(P), 1182(CL), 1183(CR)				
Gas type-pressure	Natural gas G25.3 – 25 mbar	Natural gas G20 – 20 mbar	Natural gas G25 – 20 mbar	LPG G30/31- 28-50 mbar	
Heat input (kW)	10.9	11.5	9.5	11.9	
Heat output max (kW)	8.9	9.4	7.8	9.8	
Heat output min (kW)	2.6	2.6	2.5	2.6	
Consumption (m³/h and kg/h LPG)	1.3	1.2	1.14	0.8	
Efficiency (%)	82	82	83	82	
Energy label highest efficiency	В	В	В	В	
Flue lay out wall termination	Indirect 1m vertical and max 5.5m horizontal				
Weight (kg)	200				
Efficiency class EN613	1				
NOx Class	5				
PIN ID CE	0461CT1094				
Gas connection	3/8" outside connection				
Electrical connection	6VDC battery powered				
Gas control system	Mertik Maxitrol SYMAX B6R radio controlled 866 mHz				
Safety	Thermocouple flame supervision and pressure hatches				
Heat distribution	Internal convection system				
Connectivity	Optional App control (Android and IOS), wall switch and domotica connection				
Flue type and diameter	Holetherm-CC concentric flue 130-200mm				
Standard supplied	Adjustable legs - Convection chamber and grills - Wall brackets - Log set				
Optional	Support iron for brickwork chimneybreast				
Remarks		Always use non-combustible construction materials such as metal stud framing and fireboard cladding			

Installation details

Concentric flue system

Using the THC-CC double wall chimney system the flue gases are safely transported to the outside and fresh combustion-air is pulled inside the appliance. Balanced flue appliances can be installed using a wall terminal so no traditional chimney is needed. THC-CC is made of high quality stainless steel and approved according CE standards in combination with the Trimline appliances.



Balanced flue gas fire

One of the most innovative aspects of the Trimline 83 series is that there is no need for an existing chimney to be present. This is all down to the clever features of our balanced flue gas fire, that is fully room sealed. Not only does this make for a highly efficient and safe appliance, but when combined with our concentric flue system, our fires can be positioned in virtually any part of your home with a relatively simple 'chimney breast' built around it. A direct wall outlet from the back of the fire makes the installation even easier.

