## Trimline 83 Tunnel

#### A VISUAL STATEMENT. PERFECT TO DIVIDE TWO SPACES



What is more magical then a fire visible from different rooms? This tunnel fireplace is designed to give you that ultimate feeling of being home. It gives your house an extra dimension, perfect to enjoy the fire with people you love and create special moments together.

The standard version of this fireplace has a burner bed made of wooden logs and is equipped with a double burner. You can also opt for a built-in LED bed to add even more ambiance. The Trimline 83 Tunnel also comes in a Room Divider version. On top of that, it comes with the Ecomax remote control and you have the options of adding Wi-Fi-control with our Trimline Fires app.



# trimline

## Product specifications

#### **FEATURES**



Balanced flue gas fire



Tunnel model



Woodburner with double burner



Ecomax remote control



Antracite steel panel

#### **OPTIONALS**



LED glowing fuel bed



Wall bracket remote control



Black glass interior



Grooved interior





Anti reflective glass



Mains adapter GV60



Puck control

Wi-Fi remote app

Domotica smart

Wall switch

## Styling & Optionals

#### Ecomax remote control

For absolute ease of use all appliances are supplied with an Ecomax remote system that controls the fire at the touch of a button.



#### Options interior finish materials and Trimline Wi-Fi control

For that extra WOW factor, there is also an option to upgrade to a black glass lining within the combustion chamber which offers a remarkable effect of added depth and detail. Other available upgrades also include Wi-Fi, anti reflective glass.







Appliance name	Trimline 83 Tunnel				
Appliance type	Balanced flue built-in gas fires (C11, C31, C91)				
Purpose	Ambient heating, real flames				
Engine identification	1185 (TL)				
Gas type-pressure	Natural gas G25.3-25mbar	Natural gas G20-20mbar	Natural gas G25-20mbar	LPG G30/31-28-50mbar	
Heat input (kW)	11,8	12,2	10,2	13,9	
Heat output max (kW)	9,6	10,2	8,4	11,5	
Heat output min (kW)	3,4	3,7	3,7	3,5	
Consumption (m³/h and kg/h LPG)	1,4	1,3	1,3	0,8	
Efficiency (%)	83	83	83	83	
Energy label highest efficiency	В	В	В	В	
Flue lay out wall termination	Indirect 1m vertical and max 5,5m horizontal / LPG max 3m horizontal				
Weight (kg)	225				
Efficiency class EN613	2				
NOx Class	4				
PIN ID CE	0461CV1116				
Gas connection	3/8" outside connection				
Electrical connection	6 VDC battery powered				
Gas control system	Mertik Maxitrol SYMAX B6R radio controlled 866 mHz				
Safety	Thermocouple flame supervision and pressurehatches				
Heat distribution	Internal convection system				
Connectivity	Optional App control (Android and IOS). Wallswitch and domotica connection				
Flue type and diameter	Holetherm-CC concentric flue 130-200mm				
Standard supplied	Adjustable legs - Convection chamber and grills - Wall brackets - Log set				
Optional	Support iron for brickwork chim	Support iron for brickwork chimneybreast – Black Glass interior – Rilled interior			
Remarks	Always use non-combustible co	Always use non-combustible construction materials such as metal stud framing and fireboard cladding			

## Installation details

## Concentric flue system

Using the THC-CC double wall chimney system the flue gases are safely transported to the outside and fresh combustion-air is pulled inside the appliance. Balanced flue appliances can be installed using a wall terminal so no traditional chimney is needed. THC-CC is made of high quality stainless steel and approved according CE standards in combination with the Trimline appliances.



## Balanced flue gas fire

One of the most innovative aspects of the Trimline 83 Tunnel is that there is no need for an existing chimney to be present. This is all down to the clever features of our balanced flue gas fire, that is fully room sealed. Not only does this make for a highly efficient and safe appliance, but when combined with our concentric flue system, our fires can be positioned in virtually any part of your home with a relatively simple 'chimney breast' built around it. A direct wall outlet from the back of the fire makes the installation even easier.

