



Trimline 120 Room Divider



Discover the Trimline 120 Room Divider – our latest gas fireplace that perfectly combines atmosphere and design. This unique see-through fireplace is equipped with realistically burning logs, which ensures a warm, authentic look. Thanks to the optional LED bed, the fire gets extra depth and a modern touch, even when the fireplace is switched off. A real eye-catcher that stylishly connects rooms and creates atmosphere all year round.

Technical specifications

Type of indication(s)		Trimline 120 Roomdivider-Tunnel-Roomdivider 3/4- Corner (1160-1165)			
Appliance type		C11	C31	C91	
Symbol	Concentric extraction system	Holetherm CC 130 - 200			
	Gas type		G30/G31	G30	G30
					ADJUST WHEN USED
	Country		BE/CH/CY/CZ/ES/FR/GB /GR/IE/IT/LT/NL/NO/PT/ SI/SK/TR/	CY/CZ/DK/EE/FR/GB /HR/HU/IT/LT/PL/RO /SE/SI/SK/	CY/CZ/DK/EE/FR/GB/H R/HU/IT/LT/PL/RO/SE/ SI/SK/
	Category		B+	B/P	B/P (50mbar)
		0			If burner pressure is 50mbar, adjust burner pressure high and low
	Primary air per burner	mm	L=4xØ8 M=4xØ8,5 R=4xØ8 Main=3xØ11		
Pnom	Supply pressure	mbar	(28-30)-37	30	50
Pb-High	Burner pressure - high position	mbar	27,35	27,35	27,35
Pb-low	Burner pressure - low position	mbar	14,19	14,19	14,19
	Injector orifice	Ø mm	L=0,75 M=0,75 R=0,75 Main=1,45		
	Pilot lame injector	CODE	221		
	Low position orifice	mm	Adjustable		
Qn	Load Hs	kW	14,61	14,61	14,61
Qn	Load Hi	kW	13,48	13,48	13,48
Vmax	Gas consumption	m³/h	0,418	0,418	0,418
Vmax	Gas consumption	kg/h	0,79	0,79	0,79
Vpilot	Gas consumption	m³/h	0,0075	0,0075	0,0075
Pnom Hi	Nominal power - high position	kW	10,44	10,44	10,44
Pmin Hi	Nominal power - low position	kW	4,78	4,78	4,78
	NOx classes	Hi	5	5	5
	NOx Hs	mg/kWh	48,66	48,66	48,66

Dimensional drawings

